

swiss lifting solutions QUESTION FORM GIS ELECTRIC CHAIN HOIST

Customer data			
Company		Date	
Adress		Customer number	
Postal code		Phone number	
City - Country		Fax number	
Responsible person		Function	
GIS Electric chain hoist			
Туре		Load capacity	kg
Lifting speed	1 speed	2 speeds	m/min
Required lifting height (standa	ard 3 m)	m 🗌 Chain bucket (option)	
Control cable length (standard 1.8 m) m			hours
Voltage		· · · ·	
Operating voltage	🗌 3 Ph 400V, 50Hz	🗌 1 Ph 230V, 50Hz	□ VHz
Location of the hoist			
Workshop	outdoor	near acids/alkaline solut	tions
Suspension			
Eyebolt suspension (stan	idard)	Hook suspension (option	n)
Carriage			
Movement of the trolley	push type	electrical type	with brake
MOvement of the troney	1 speed	2 speeds	
	— .	— ·	
Crane rail available / flang		mr	m 🔄 with traction limit
Power supply		Trailing cable	
Crane rail/power supply n		mr	—
Power supply		Trailing cable	C-rail
- · · · · · · · · · · · · · · · · · · ·	Contact line		
Suspension distance		given	mm
Sketch with suspension points enclosed!			
Additional technical data/Customer requirements			
Required offer			
Short offer	Approximate price	Offer required by	
Detailed offer	Date of realisation / des		
DELACCO d.o.o.		Enclosures	
industrial lifting equipment		Sketch	
10450 Jastrebarsko, Croatia		Plan/Drawing	
Phone +385 91 20 40 800			
			25.00.45 5-05.00
E-mail sales@delacco.com			25.08.15 Fo 85.09